

# CRATHCO Autofill

**No More Refilling.  
No More Downtime.**

NEW I-PRO Autofill Lids designed to instantly automate your current I-PRO system and your beverage programs.



Ideal for Bag-in-Box  
& In-House  
Concentrate Programs



I-PRO AUTOFILL LID

CRATHCO

# I-PRO AUTOFILL LID

## Streamline Beverage Operations

Replace your current I-PRO lid with Crathco's Autofill Lid System. Your frozen offerings will always be fresh and available, enticing customers all day long.

- **Increased Visual Appeal** – always available, increasing sales
- **Enhanced Accuracy and Consistency** – automatically adds the perfect amount of water and syrup every time
- **Reduced Labor** – keeps staff focused on customers
- **Minimizes Training** – simple set-up and operation
- **Reduced Downtime** – manual re-filling is time-consuming
- **Increased Food Safety** – minimal exposure to product
- **Seamless Integration** – update existing equipment or your entire system
- **Waste Reduction** – prevents loss from incorrectly mixed product
- **Versatile** – perfect for BIB or in-house syrup programs




**Crathco Autofill Lid  
Puts a Lid on Labor**



### HERE'S HOW AUTOFILL WORKS

*Parts included: 1 water regulator, 2@1/4" fitting threads, 3/8" tubing, 1 pressure gauge, 2@3/8" elbow coupling connector tubing*

- Automatically senses drink volume through integrated lid sensor.
- When level falls below the probe, fill tube automatically refills the bowl with the perfect blend of BIB syrup and water.
- Post Mix process mixes beverage syrup in the bowl.
- "Sold Out" switch alerts operator (by red indicator lights) syrup is low or water connection needs attention.
- Beverage syrup ratio can be set to specific needs. Controlled by gas pressure and reducing valve.



### SPECIFICATIONS

Model	Description	Electrical	Product Dimensions H x W x D	Shipping Dimensions H x W x D	Product Wt.	Shipping Wt.
LV600697	Autofill I-PRO AFI-P2-16, Black	120V 60hz 1ph 3A	10.6" x 7.4" x 15.8"*	18.3" x 19" x 11.3"	P2 - 6.86 lbs	16 lbs
LV606106	Autofill I-PRO AFI-P3-16, Black	120V 60hz 1ph 3A	10.6" x 7.4" x 15.8"*	19" x 24.8" x 11.3"	P3 - 10.29 lbs	22.7 lbs

Water Supply: Min 30psi/Max 120psi • CO<sub>2</sub>: Max 60psi • Low Pressure Cut-Off: <5psi

Compatible with Existing I-PRO 2 Units – 2M w/Light Panel | 2M UV 2 w/ Light Panel | 2E w/Light Panel | 2E UV w/Light Panel | 2E UV

\*Includes Water Level Probe

Part of  **Electrolux  
Professional  
Group**

**CRATHCO**

169/3, Moo. 3, Tambol Nonglajok, Amphur Ban Khai,  
Rayong 21120, Thailand,

[www.crathco.com](http://www.crathco.com)